

# TECHNICAL DATA SHEET

**CODE:** ANT0666

**NAME:** ANT0666 VEICOLO PER ANTICATURE PAIETTABILI

**GROUP:** SOLVENT BASED CONVERTER

## CHARACTERISTICS

Solvent-based converter for antique effect finishing for application with a spray gun on wood veneer, characterised by fast drying and good light resistance.

To protect this stain, polyurethane varnish, "nitro" varnish, polyester varnish or water-based varnish can be applied.

## TECHNICAL SPECIFICATIONS

ANT0600 Series	Property	Specification	Units	Method
	Density (20°C)	0,94 - 0,98	gr/cc	IST 11/01
	Viscosity, Ford Cup 4 (20°C)	09 - 12	Sec.	IST 11/08
	Solid Content	20 - 24	%	IST 11/06

*The values describe the typical properties of the product. Technical Specifications are available upon request.*

## USE

The solvent-based converter is ready to use and it can be coloured in various shades through the addition of product from the PPT 02 series for about 10% of the weight.

It is recommended to stir the product well before and during use.

## APPLICATION

Dust free	About 15' at 20°C (with good ventilation)
Overcoating	After 4 hours at 20°C (with good ventilation)

## STORAGE AND PACKAGING PRECAUTIONS

Keep it tightly sealed in its original container in a cool environment (between 4°C and 40°C) that is not subject to abrupt temperature excursions.

Standard packaging size of 25 Kg; for other requests a feasibility evaluation will be made.

## SAFETY PRECAUTIONS

The product is intended for professional use only, refer to the Safety Data Sheet.

MOD. 11 - 08 (Rev. 1 - 06/2016)

The data shown refers to laboratory tests, in practical applications these can change slightly according to the working conditions. The user must anyway check the suitability of the product for its expected use, taking upon himself all responsibility arising from its use. Sigmar reserves the right to introduce technical changes without prior notice.