

# TECHNICAL DATA SHEET

**CODE:** APV0071

**NAME:** APV0071 - BESCHLEUNIGER 10 TIX-NON-TIX

**GROUP:** ACCELERATOR

## CHARACTERISTICS

Liquid accelerator additive for industrial applications, specific for unsaturated polyester products. The additive can also be used as accelerator for alkyd-based paints and drying oils in order to accelerate the drying of the film.

## TECHNICAL SPECIFICATIONS

APV0071	Property	Specification	Units	Method
	Density (20°C)	0,91 - 0,95	gr/cc	IST 11/01
	Viscosity, Ford Cup 4 (20°C)	09 - 11	Sec.	IST 11/08

## USE

Depending on the Insaturated-Polyesters Varnish used.

The added amount depends on the normal drying speed of the product and is however deductible through practical tests.

Stir well after adding.

## APPLICATION

The application characteristics can only be evaluated in combination with the paint that is used.

## STORAGE AND PACKAGING PRECAUTIONS

Keep it tightly sealed in its original container in a cool environment (between 4°C and 40°C) that is not subject to abrupt temperature excursions.

Standard pack size is 0.5 Kg. For other specific requirements a feasibility evaluation will be made.

## SAFETY PRECAUTIONS

The product is intended for professional use only, refer to the Safety Data Sheet.

MOD. 11 - 08 (Rev. 1 - 06/2016)

The data shown refers to laboratory tests, in practical applications these can change slightly according to the working conditions. The user must anyway check the suitability of the product for its expected use, taking upon himself all responsibility arising from its use. Sigmar reserves the right to introduce technical changes without prior notice.