

# TECHNICAL DATA SHEET

**CODE:** APV0110

**NAME:** APV0110 - ADDITIVO ANTICRATERE

**GROUP:** ANTI-CRATER ADDITIVE

## CHARACTERISTICS

Surface additive for solvent systems, with a strong reduction in surface tension, very effective for wetting critical supports and to avoid craters.

Non ha nessuna influenza sulle proprietà di "slip" della superficie.

## TECHNICAL SPECIFICATIONS

APV0110	Property	Specification	Units	Method
	Density (20°C)	0,88 - 0,92	gr/cc	IST 11/01
	Viscosity, Ford Cup 4 (20°C)	09 - 11	Sec.	IST 11/08
	Solid Content	01 - 04	%	IST 11/06

*The values describe the typical properties of the product. Technical Specifications are available upon request.*

## USE

The APV0110 product is added from 1 to 5% in weight, on the total weight of the formulation. In exceptional cases it can be added up to 10% in weight.

## APPLICATION

The application characteristics can only be evaluated in combination with the paint that is used.

## STORAGE AND PACKAGING PRECAUTIONS

Keep it tightly sealed in its original container in a cool environment (between 4°C and 40°C) that is not subject to abrupt temperature excursions.

Standard pack size is 1 Kg. For other specific requirements a feasibility evaluation will be made.

## SAFETY PRECAUTIONS

The product is intended for professional use only, refer to the Safety Data Sheet.

MOD. 11 - 08 (Rev. 1 - 06/2016)

The data shown refers to laboratory tests, in practical applications these can change slightly according to the working conditions. The user must anyway check the suitability of the product for its expected use, taking upon himself all responsibility arising from its use. Sigmar reserves the right to introduce technical changes without prior notice.