

TECHNICAL DATA SHEET

CODE: HIE1265

NAME: HIE1265 WOOD CLEANER SIGMAR-BIO

GROUP: ADDITIVO

CHARACTERISTICS

HIE1265 WOOD CLEANER SIGMAR-BIO is a water-based additive for restoring the original color of outdoor wooden products that have turned gray due to the action of outdoor weathering. Easily to apply both by spray-gun and paint-brush, it is suitable on exterior flooring, garden furniture, wooden claddings, fences, wooden beams.

HIE1265 WOOD CLEANER SIGMAR-BIO is 99,4% biodegradable.

TECHNICAL SPECIFICATIONS

HIE1265	Property	Specification	Units	Method
	Solid Content	4,0 - 6,0	%	IST 11/06
	Viscosity, Ford Cup 4 (20°C)	24 - 30 Sec.	%	IST 11/08
	pH	1 - 3	pH	IST 11/03

The values describe the typical properties of the product. Technical Specifications are available upon request.

USE

It is recommended to stir well the product before use. Carry out a preliminary test on a small area of the surface to be treated. Remove any traces of paint and dirt from the surface to be treated. Before starting the treatment, wet, by spraying or with a brush, the surface with water to avoid excessive absorption of the product into the wood.

The product is ready-to-use, Apply HIE1265 WOOD CLEANER SIGMAR-BIO by a paint brush or a pennello o a spruzzo fino a formare uno strato di circa un millimetro. Wait 15-20 minutes after applying, then brush carefully along the the wood grain to remove the layer that has formed using a scrubbing brush with sufficiently hard fibres, for example broomcorn or plastic (do not use metal brushes). Finally rinse thoroughly with water using the brush to remove residues.

For very weathered and grayed wood, repeat the treatment a second time..

Once the treatment is completed, leave the surface to dry for at least 48 hours before painting.

Strongly weathered and damaged surfaces may require sanding before painting (180-240 grit sandpaper recommended).

STORAGE AND PACKAGING PRECAUTIONS

Keep it tightly sealed in its original container in a cool environment (between + 4°C and + 35°C) that is not subject to abrupt temperature excursions.

Standard pack size is 1 Kg. For other specific requirements a feasibility evaluation will be made.

SAFETY PRECAUTIONS

The product is intended for professional use only, refer to the Safety Data Sheet.

MOD. 11 - 08 (Rev. 1 - 06/2016)

The data shown refers to laboratory tests, in practical applications these can change slightly according to the working conditions. The user must anyway check the suitability of the product for its expected use, taking upon himself all responsibility arising from its use. Sigmar reserves the right to introduce technical changes without prior notice.