

TECHNICAL DATA SHEET

CODE: PPS0064

NAME: PPS0064 - PASTA BIANCA HYDRO

GROUP: CONCENTRATED PIGMENT PASTE

CHARACTERISTICS

White pigmented paste in an aqueous suspension, for use in the wood industry in small quantities to correct defects in wood veneer or in medium quantities for formulating coloured dyes.

TECHNICAL SPECIFICATIONS

PPS0064	Property	Specification	Units	Method
	Density (20°C)	2,06 - 2,10	gr/cc	IST 11/01

The values describe the typical properties of the product. Technical Specifications are available upon request.

USE

The pigmented paste can be added to the topcoat in the order of 5% maximum to correct defects due to the veneer or added in a maximum concentration of 30% to a water formulation to prepare coloured dyes. Stir well after adding.

APPLICATION

The pigmented paste can be applied either by spraying or by rag/brush.

STORAGE AND PACKAGING PRECAUTIONS

Keep it tightly sealed in its original container in a cool environment (between - 5°C and + 30°C) that is not subject to abrupt temperature excursions.

Standard pack size is 1 Kg. For other specific requirements a feasibility evaluation will be made.

SAFETY PRECAUTIONS

The product is intended for professional use only, refer to the Safety Data Sheet.

MOD. 11 - 08 (Rev. 1 - 06/2016)

The data shown refers to laboratory tests, in practical applications these can change slightly according to the working conditions. The user must anyway check the suitability of the product for its expected use, taking upon himself all responsibility arising from its use. Sigmar reserves the right to introduce technical changes without prior notice.