

TECHNICAL DATA SHEET

CODE: PPS0353

NAME: PPS0353 - PASTA BLACK FOR PIANO LOOK

GROUP: CONCENTRATED PIGMENT PASTE

CHARACTERISTICS

Solvent-based black pigment paste for use in the wood industry in small quantities to colour varnish based on unsaturated polyester.

TECHNICAL SPECIFICATIONS

PPS0353	Property	Specification	Units	Method
	Density (20°C)	1,08 - 1,12	gr/cc	IST 11/01
	Viscosity, Ford Cup 4 (20°C)	Thixotropic ($t \geq 180''$)	Sec.	IST 11/08
	Solid Content	90 - 100	%	IST 11/06

The values describe the typical properties of the product. Technical Specifications are available upon request.

USE

Add the pigmented paste to the unsaturated polyester based paint in a variable amount between 1 and 3 wt %, depending on the desired effect. It is recommended to stir it well for 5 minutes after its addition.

APPLICATION

Evaluate depending on the paint used with the PPS0353.

STORAGE AND PACKAGING PRECAUTIONS

Keep it tightly sealed in its original container in a cool environment (between + 20°C and + 30°C) that is not subject to abrupt temperature excursions.

Standard pack size is 1 Kg. For other specific requirements a feasibility evaluation will be made.

SAFETY PRECAUTIONS

The product is intended for professional use only, refer to the Safety Data Sheet.

MOD. 11 - 08 (Rev. 1 - 06/2016)

The data shown refers to laboratory tests, in practical applications these can change slightly according to the working conditions. The user must anyway check the suitability of the product for its expected use, taking upon himself all responsibility arising from its use. Sigmar reserves the right to introduce technical changes without prior notice.