

TECHNICAL DATA SHEET

CODE: PPS0387

NAME: PPS0387 - PIGMENT PASTE BRUNO BRME2M

GROUP: CONCENTRATED PIGMENT PASTE

CHARACTERISTICS

Solvent-based brown pigment paste for use in the wood industry in small quantities to colour sealers and primers made from saturated polyester or polyurethane resins.

TECHNICAL SPECIFICATIONS

PPS0387	Property	Specification	Units	Method
	Density (20°C)	0,83 - 0,87	gr/cc	IST 11/01
	Viscosity, Ford Cup 4 (20°C)	16 - 20	Sec.	IST 11/08
	Solid Content	08 - 12	%	IST 11/06

The values describe the typical properties of the product. Technical Specifications are available upon request.

USE

Add the pigmented paste to the saturated polyester or polyurethane sealer in a variable amount between 10 and 20%, depending on the desired effect. Stir well after adding.

APPLICATION

Assessable only in combination with saturated polyester or polyurethane sealer.

STORAGE AND PACKAGING PRECAUTIONS

Keep it tightly sealed in its original container in a cool environment (between - 5°C and + 30°C) that is not subject to abrupt temperature excursions.

Standard pack size is 1 Kg. For other specific requirements a feasibility evaluation will be made.

SAFETY PRECAUTIONS

The product is intended for professional use only, refer to the Safety Data Sheet.

MOD. 11 - 08 (Rev. 1 - 06/2016)

The data shown refers to laboratory tests, in practical applications these can change slightly according to the working conditions. The user must anyway check the suitability of the product for its expected use, taking upon himself all responsibility arising from its use. Sigmar reserves the right to introduce technical changes without prior notice.