

TECHNICAL DATA SHEET

CODE: PPT 02 Series

NAME: PPT 02 Series - PASTES

GROUP: PIGMENTED PASTES

CHARACTERISTICS

Solvent-based colouring paste, usable in combination with converters, both acrylic and polyurethane, in order to obtain lacquer paints.

Available in various colour tones.

TECHNICAL SPECIFICATIONS

The technical specifications are supplied on request, according to colour.

USE

The solvent-based pigmented pastes from the PPT 02 Series may be added to converters, both acrylic and polyurethane, according to the following recommendation:

- KOPP white converters at 95% by weight + PPT 02 Series pigmented pastes at 5% by weight.
 - KOPT o KOAT clear converters at 75% by weight + PPT 02 Series pigmented pastes at 25% by weight.
- Refer to the data sheets of the converters, for the preparation and final characteristics of mixed products.

APPLICATION

The pigmented pastes from the PPT 02 Series when mixed with the appropriate converter can be applied by airless spray, airmix or gravity cup.

STORAGE AND PACKAGING PRECAUTIONS

Keep it tightly sealed in its original container in a cool environment (between 4°C and 40°C) that is not subject to abrupt temperature excursions.

Standard pack size is 1 Kg. For other specific requirements a feasibility evaluation will be made.

SAFETY PRECAUTIONS

The product is intended for professional use only, refer to the Safety Data Sheet.

MOD. 11 - 08 (Rev. 1 - 06/2016)

The data shown refers to laboratory tests, in practical applications these can change slightly according to the working conditions. The user must anyway check the suitability of the product for its expected use, taking upon himself all responsibility arising from its use. Sigmar reserves the right to introduce technical changes without prior notice.