

TECHNICAL DATA SHEET

CODE: PTS0014

NAME: PTS0014 - PASTA TESTURIZZANTE FINE

GROUP: TEXTURING PASTES

CHARACTERISTICS

Fine texturizing paste, for applications on wood or woody materials, to use in small quantities in solvent-based Varnish, Polyuretanics or Acrylics to lend to the varnished surfaces a rough, but pleasant to the touch, texture.

TECHNICAL SPECIFICATIONS

PPT0014	Property	Specification	Units	Method
	Density (20°C)	0,90 - 0,94	gr/cc	IST 11/01
	Viscosity, Ford Cup 4 (20°C)	Thixotropic (t _{>} = 180")	Sec.	IST 11/08
	Solid Content	52 - 56	%	IST 11/06

The values describe the typical properties of the product. Technical Specifications are available upon request.

USE

Add the PTS texturizing paste in a quantity equal to 10% to the paint to Texturize. It is recommended to stir it well for 5 minutes after its addition. Proceed with hardening, thinning and applying, following the specific indications of the paint used.

APPLICATION

Evaluable depending on the paint used with it.

STORAGE AND PACKAGING PRECAUTIONS

Keep it tightly sealed in its original container in a cool environment (between - 5°C and + 30°C) that is not subject to abrupt temperature excursions.

Standard pack size is 1 Kg. For other specific requirements a feasibility evaluation will be made.

SAFETY PRECAUTIONS

The product is intended for professional use only, refer to the Safety Data Sheet.

MOD. 11 - 08 (Rev. 1 - 06/2016)

The data shown refers to laboratory tests, in practical applications these can change slightly according to the working conditions. The user must anyway check the suitability of the product for its expected use, taking upon himself all responsibility arising from its use. Sigmar reserves the right to introduce technical changes without prior notice.