

TECHNICAL DATA SHEET

CODE: SML0174

NAME: SML0174 - STUCCO TRASPARENTE

GROUP: FILLER

CHARACTERISTICS

Single component filler for wood retouch, for spatula applications on wood or woody materials, characterised by excellent filling and good sandability. Suitable to correct wood defects as cracks, knots, or assembly defects. Intended for interiors applications

TECHNICAL SPECIFICATIONS

SML0174	Property	Specification	Units	Method
	Solid Content	26 -32	%	IST 11/06

The values describe the typical properties of the product. Technical Specifications are available upon request.

USE

The single-component CLEAR filler is ready for use, for spatula applications.

APPLICATION

Sandable	About 3 hours at 20°C (with good ventilation)
Overcoating	After about 3 hours at 20°C (with good ventilation)

STORAGE AND PACKAGING PRECAUTIONS

Keep it tightly sealed in its original container in a cool environment (between - 5°C and + 40°C) that is not subject to abrupt temperature excursions.

Standard pack size is 1 Kg. For other specific requirements a feasibility evaluation will be made.

SAFETY PRECAUTIONS

The product is intended for professional use only, refer to the Safety Data Sheet.

MOD. 11 - 08 (Rev. 1 - 06/2016)

The data shown refers to laboratory tests, in practical applications these can change slightly according to the working conditions. The user must anyway check the suitability of the product for its expected use, taking upon himself all responsibility arising from its use. Sigmar reserves the right to introduce technical changes without prior notice.