

TECHNICAL DATA SHEET

CODE: SML0373

NAME: SML0373 - HOLZSPECHTELLACK TRANSP.

GROUP: FILLER

CHARACTERISTICS

Single component filler for wood retouch, for spatula applications on wood or woody materials, characterised by excellent filling and good sandability. Suitable to correct wood defects as cracks, knots, or assembly defects. Intended for interiors applications

TECHNICAL SPECIFICATIONS

SML0373	Property	Specification	Units	Method
	Solid Content	24,0 - 28,0	%	IST 11/06
	Density (20°C)	0,89 - 0,93	%	IST 11/01

The values describe the typical properties of the product. Technical Specifications are available upon request.

USE

Add the wood dust to the filler, under strong stirring, in a such amount as to make the product suitable for processing, or mix small amount of the filler with wood dust using a spatula.

After mixing the filler with the wood dust, the product is easily applied with a spatula.

APPLICATION

Sandable	About 3 hours at 20°C (with good ventilation)
Overcoating	After about 3 hours at 20°C (with good ventilation)

STORAGE AND PACKAGING PRECAUTIONS

Keep it tightly sealed in its original container in a cool environment (between - 5°C and + 40°C) that is not subject to abrupt temperature excursions.

Standard pack size is 1 Kg. For other specific requirements a feasibility evaluation will be made.

SAFETY PRECAUTIONS

The product is intended for professional use only, refer to the Safety Data Sheet.

MOD. 11 - 08 (Rev. 1 - 06/2016)

The data shown refers to laboratory tests, in practical applications these can change slightly according to the working conditions. The user must anyway check the suitability of the product for its expected use, taking upon himself all responsibility arising from its use. Sigmar reserves the right to introduce technical changes without prior notice.