

# TECHNICAL DATA SHEET

**CODE:** SML Series

**NAME:** SML Series - FILLER

**GROUP:** FILLER

## CHARACTERISTICS

Single component filler for wood, characterized by minimum loss of thickness and good sandability. Ideal to repair small defects in the wood.

Intended for interior applications, available in various colour tones.

## TECHNICAL SPECIFICATIONS

SML Series	Property	Specification	Units	Method
	Solid Content	60 - 70	%	IST 11/06

*The values describe the typical properties of the product. Technical Specifications are available upon request.*

## USE

The single-component filler from the SML series is ready for use, for spatula applications.

## APPLICATION

Sandable	About 3 hours at 20°C (with good ventilation)
Overcoating	After about 3 hours at 20°C (with good ventilation)

## STORAGE AND PACKAGING PRECAUTIONS

Keep it tightly sealed in its original container in a cool environment (between - 5°C and + 40°C) that is not subject to abrupt temperature excursions.

Standard pack size is 1 Kg. For other specific requirements a feasibility evaluation will be made.

## SAFETY PRECAUTIONS

The product is intended for professional use only, refer to the Safety Data Sheet.

MOD. 11 - 08 (Rev. 1 - 06/2016)

The data shown refers to laboratory tests, in practical applications these can change slightly according to the working conditions. The user must anyway check the suitability of the product for its expected use, taking upon himself all responsibility arising from its use. Sigmar reserves the right to introduce technical changes without prior notice.