

# TECHNICAL DATA SHEET

**CODE:** UAT1426

**NAME:** UAT1426 - 1K ACRYLIC MULTILAYERLACK/25

**GROUP:** CLEAR ACRYLIC VARNISH

## CHARACTERISTICS

Solvent-based multi-layer clear acrylic paint, for application with spray, brush and roller, characterised by a high resistance to mechanical stresses.

Intended for interiors applications on solid or veneered wood furnitures.

## TECHNICAL SPECIFICATIONS

UAT1426	Property	Specification	Units	Method
	Density (20°C)	0,93 - 0,97	gr/cc	IST 11/01
	Viscosity, Ford Cup 4 (20°C)	74 - 86	Sec.	IST 11/08
	Solid Content	25 - 31	%	IST 11/06

*The values describe the typical properties of the product. Technical Specifications are available upon request.*

## USE

The product is ready for use; thin with DPV006 to reach the application viscosity. The thinning of the product is established at the time of application according to the application parameters present, recommended at 20% by weight. When a better product spreading is required, it is recommended to add a small amount of retardant thinner DPV0026 to the mix.

## APPLICATION

Amount for single layer.	90 - 110 gr/m <sup>2</sup>
Dust free	About 10'-15' at 20°C (with good ventilation)
Sanding	After about 4 hours at 20°C (with good ventilation)
Stacking	After 24 hours (with good ventilation)
Gloss Level	22 - 28 Gloss Units

## STORAGE AND PACKAGING PRECAUTIONS

Keep it tightly sealed in its original container in a cool environment (between - 5°C and + 40°C) that is not subject to abrupt temperature excursions.

Standard packaging size of 25 Kg; for other requests a feasibility evaluation will be made.

## SAFETY PRECAUTIONS

The product is intended for professional use only, refer to the Safety Data Sheet.

MOD. 11 - 08 (Rev. 1 - 06/2016)

The data shown refers to laboratory tests, in practical applications these can change slightly according to the working conditions. The user must anyway check the suitability of the product for its expected use, taking upon himself all responsibility arising from its use. Sigmar reserves the right to introduce technical changes without prior notice.